

Fisa tehnica Midea mono-split Caseta tavan R32

Model			MCD-18FNXD0/MOU-18FN8-QD0	MCD-24FNXD0/MOU-24FN8-QD0	MCD-36FNXD0/MOU-36FN8-QD0
Alimentare unitate interioara		Ph-V-Hz	220-240V~ 50Hz, 1Ph	220-240V~ 50Hz, 1Ph	220-240V~ 50Hz, 1Ph
Alimentare unitate exterioara		Ph-V-Hz	220-240V~ 50Hz, 1Ph	220-240V~ 50Hz, 1Ph	220-240V~ 50Hz, 1Ph
Capacitate	Racire (min/max)	Btu/h	18000(4300-21000)	24000(7600-28000)	35100(9000-41000)
		kW	5.3(1.26-6.15)	7.0(2.23-8.21)	10.3(2.64-12.02)
	Incalzire (min/max)	Btu/h	19000(6000-24000)	25200(8300-29500)	37000(10000-45000)
		kW	5.57(1.76-7.03)	7.39(2.43-8.65)	10.86(2.93-13.19)
Putere alimentare	Racire (min/max)	W	1640(280-2150)	2190(480-2850)	3810(660-4500)
	Incalzire (min/max)	W	1500(330-2180)	1980(500-2880)	3000(650-4550)
Curent nominal	Racire (min/max)	A	7.1(1.2-9.3)	9.5(2.1-12.4)	16.6(2.9-19.6)
	Incalzire (min/max)	A	6.5(1.4-9.5)	8.9(2.2-12.5)	12.9(2.8-19.8)
SEER/SCOP		W/W	6.1 / 4	6.1 / 4	6.1 / 4
Clasa de eficienta Energetica	Racire		A++	A++	A++
	Incalzire (min/max)		A+	A+	A+
<b>Unitate interioara</b>					
Debit (Hi/Mi/Lo)		m3/h	1036/867/763	1378/1200/1032	1775/1620/1438
Nivel de presiune sonora (Hi/Mi/Lo)		dB(A)	46/41/37	47/43/40	52/49/46
Nivel de putere sonora (Hi)		dB(A)	57	60	63
Dimensiune unitate	(L*A*I)	mm	840x840x205	840x840x205	840x840x245
Dimensiune ambalaj	(L*A*I)	mm	900x900x225	900x900x225	900x900x265
Dimensiune panel	(L*A*I)	mm	950x950x55	950x950x55	950x950x55
Dim. Ambalaj panel	(L*A*I)	mm	1035x1035x90	1035x1035x90	1035x1035x90
Greutate unitate	neta/bruta	Kg	21.4/25.1	23/27	27.5/31
Greutate panel	neta/bruta	Kg	5/8	5/8	5/8

Model			MCD-36FNXD0/MOU-36FN1-RD0	MCD-55FNXD0/MOU-55FN8-RD0
Alimentare unitate interioara		Ph-V-Hz	220-240V~ 50Hz, 1Ph	220-240V~ 50Hz, 1Ph
Alimentare unitate exterioara		Ph-V-Hz	220-240V~ 50Hz, 3Ph	220-240V~ 50Hz, 3Ph
Capacitate	Racire (min/max)	Btu/h	36000(9000-41000)	53600(18000~57000)
		kW	10.5(2.64-12.02)	15.7(5.28~16.71)
	Incalzire (min/max)	Btu/h	37800(10000-45000)	62000(15000~66000)
		kW	11.09(2.93-13.19)	18.2(4.4~19.34)
Putere alimentare	Racire (min/max)	W	3900(660-4500)	5990(1147~6682)
	Incalzire (min/max)	W	2970(650-4550)	6030(1022~6448)
Curent nominal	Racire (min/max)	A	7.2(1.2-8.2)	10.3(1.8~11)
	Incalzire (min/max)	A	5.5(1.2-8.3)	9.9(1.6~10.6)
SEER/SCOP		W/W	6.1 / 4	6.1 / 4
Clasa de eficienta Energetica	Racire		A++	A++
	Incalzire (min/max)		A+	A+
<b>Unitate interioara</b>				
Debit (Hi/Mi/Lo)		m3/h	1775/1620/1438	1970/1737/1537
Nivel de presiune sonora (Hi/Mi/Lo)		dB(A)	52/49/46	53/50.5/48
Nivel de putere sonora (Hi)		dB(A)	63	65
Dimensiune unitate	(L*A*I)	mm	840x840x245	840x840x287
Dimensiune ambalaj	(L*A*I)	mm	900x900x265	900x900x292
Dimensiune panel	(L*A*I)	mm	950x950x55	950x950x55
Dim. Ambalaj panel	(L*A*I)	mm	1035x1035x90	1035x1035x90
Greutate unitate	neta/bruta	Kg	27.5/31	29.7/33.4
Greutate panel	neta/bruta	Kg	5/8	5/8