

Fisa tehnica Midea Duct A6 ErP R32

Model		MTI-55FNXD0/MOU-55FN8-RD0	
Alimentare unitate interioara		Ph-V-Hz	220-240V~ 50Hz, 1Ph
Alimentare unitate exterioara		Ph-V-Hz	220-240V~ 50Hz, 1Ph
Capacitate	Racire (min/max)	Btu/h	52500(20000~59000)
		kW	15.4(5.86~17.29)
	Incalzire (min/max)	Btu/h	60500(16000~70000)
		kW	17.73(4.69~20.52)
Putere alimentare	Racire (min/max)	W	5423(1274~6651)
	Incalzire (min/max)	W	5180(1042~6034)
Curent nominal	Racire (min/max)	A	8.93(2~11)
	Incalzire (min/max)	A	8.8(1.6~9.9)
SEER/SCOP		W/W	6.1 / 4
Clasa de eficienta Energetica	Racire		A++
	Incalzire (min/max)		A+
Unitate interioara			
Debit (Hi/Mi/Lo)		m3/h	2600/2210/1820
Nivel de presiune sonora (Hi/Mi/Lo)		dB(A)	54/52/50.5
Nivel de putere sonora (Hi)		dB(A)	74
Dimensiune unitate	(L*A*I)	mm	1200x874x300
Dimensiune ambalaj	(L*A*I)	mm	1405x915x355
Greutate unitate	neta/bruta	Kg	47.6/55.8