

Fisa tehnica Midea multisplit Blanc R32

| Model | | | MA-09XD0-I | MA-12NXD0-I | MA-18NXD0-I | MA-24NXD0-I |
|--|---------------------|---------|----------------------|----------------------|----------------------|----------------------|
| Alimentare | | Ph-V-Hz | 220-240V~ 50Hz, 1Ph | 220-240V~ 50Hz, 1Ph | 220-240V~ 50Hz, 1Ph | 220-240V~ 50Hz, 1Ph |
| Capacitate | Racire (min/max) | Btu/h | 9000(3500-11000) | 12000(3700-14000) | 17700(6524~20977) | 24000(9045-28163) |
| | | kW | 2.6(1.02 – 3.22) | 3.5 (1.08 – 4.1) | 5.2 (1.91 – 6.14) | 7.0 (2.65 – 8.25) |
| | Incalzire (min/max) | Btu/h | 10000(2800-11500) | 13000(3700-14400) | 19000(3522-23600) | 25000(9963-29121) |
| | | kW | 2.93 (0.82 – 3.37) | 3.74 (1.08 – 4.22) | 5.57 (1.04 – 6.91) | 7.33 (2.91 – 8.53) |
| Putere alimentare | Racire (min/max) | W | 767(100~1240) | 1185(130~1580) | 1630(649~2068) | 2434(946~3507) |
| | Incalzire (min/max) | W | 788(100~1200) | 1080(120~1580) | 1538(254~2320) | 2426(1004~3072) |
| Curent nominal | Racire (min/max) | A | 3.3(0.4-5.4) | 5.1(0.5-6.9) | 7.1(0.8~10.3) | 10.6(4.34-15.4) |
| | Incalzire (min/max) | A | 3.4(0.4-5.2) | 4.8(0.5-6.9) | 6.7(0.9~10.5) | 10.5(4.57-13.5) |
| SEER/SCOP | | W/W | 3.44 / 3.72 | 2.97 / 3.47 | 3.24 / 3.62 | 2.83 / 3.02 |
| Clasa de eficienta Energetica | Racire | | A++ | A++ | A++ | A++ |
| | Incalzire (min/max) | | A+ | A+ | A+ | A+ |
| Unitate interioara | | | | | | |
| Debit (Hi/Mi/Lo) | | m3/h | 520/460/340 | 600/500/360 | 860/690/560 | 1050/860/700 |
| Nivel de presiune sonora (Hi/Mi/Lo) | | dB(A) | 36/30/26/21 | 38/34/28/22 | 43/36/30/22 | 47/40/33/22 |
| Nivel de putere sonora (Hi) | | dB(A) | 54 | 54 | 58 | 61 |
| Dimensiune carcasa | (L*A*I) | mm | 805x205x285 | 805x205x285 | 958x223x302 | 1038x235x325 |
| Dimensiune ambalaj | (L*A*I) | mm | 870x285x360 | 870x285x360 | 1035x305x380 | 1120x405x330 |
| Greutate | neta/bruta | Kg | 7.9/10.3 | 7.9/10.3 | 10.3/13.3 | 12.8/16.2 |
| Unitate exterioara | | | | | | |
| Nivel de presiune sonora/putere sonora | | dB(A) | 55.5 / 63 | 56 / 65 | 56.5 / 65 | 60 / 69 |
| Dimensiune carcasa | (L*A*I) | mm | 700x270x550 | 700x270x550 | 800x333x554 | 845x363x702 |
| Dimensiune ambalaj | (L*A*I) | mm | 815x325x615 | 815x325x615 | 920x390x615 | 965x395x755 |
| Greutate | neta/bruta | Kg | 22.7/25.2 | 22.7/25.2 | 34/36.7 | 51.5/54.5 |
| Agent frigorific | | | R32 | R32 | R32 | R32 |
| Conexiuni tevi | lichid / gaz | mm | Φ6.35/Φ9.52 | Φ6.35/Φ9.52 | Φ6.35/Φ12.7 | Φ9.52/Φ15.9 |
| Lungime max. traseu/ Dif. Max. traseu | | m | 25 / 10 | 25 / 10 | 30 / 20 | 50 / 25 |
| Interval functionare | racire/incalzire | ° C | -15 ~ 50/-25 ~ 30 | -15 ~ 50/-25 ~ 30 | -15 ~ 50/-25 ~ 30 | -15 ~ 50/-25 ~ 30 |