

Fisa tehnica Midea Ultimate Comfort R32

Model			MT-09N8D6/MBT-09N8D6	MT-12N8D6/MBT-12N8D6
Alimentare		Ph-V-Hz	220-240V~ 50Hz, 1Ph	220-240V~ 50Hz, 1Ph
Capacitate	Racire (min/max)	Btu/h	9000(3500-11000)	12000(3700-14000)
		kW	2.6(1.02-3.22)	3.5(1.37-4.3)
	Incalzire (min/max)	Btu/h	10000(2800-11500)	13000(3000-14400)
		kW	3.0(0.82-3.37)	3.86(1.06-4.38)
Putere alimentare	Racire (min/max)	W	676(80-1100)	1005(120-1650)
	Incalzire (min/max)	W	637(70-990)	953(110-1470)
Curent nominal	Racire (min/max)	A	2.94(0.35-4.78)	4.37(0.5-7.2)
	Incalzire (min/max)	A	2.8(0.32-4.32)	4.14(0.5-6.4)
SEER/SCOP		W/W	8.2 / 4.6	7.4 / 4.6
Clasa de eficienta Energetica	Racire		A++	A++
	Incalzire (min/max)		A++	A++
<b>Unitate interioara</b>				
Debit (Hi/Mi/Lo)		m3/h	500/370/240	550/480/420
Nivel de presiune sonora (Hi/Mi/Lo/Si)		dB(A)	39.5/30/21/19.5	40.5/31/21.5/21.5
Nivel de putere sonora (Hi)		dB(A)	55	55
Dimensiune carcasa	(L*A*I)	mm	886x188x315	886x188x315
Dimensiune ambalaj	(L*A*I)	mm	985x300x385	985x300x385
Greutate	neta/bruta	Kg	10.3/13.3	10.3/13.3
<b>Unitate exterioara</b>				
Nivel de presiune sonora/putere sonora		dB(A)	55.5 / 59	55.5 / 61
Dimensiune carcasa	(L*A*I)	mm	800x333x554	800x333x554
Dimensiune ambalaj	(L*A*I)	mm	920x390x615	920x390x615
Greutate	neta/bruta	Kg	29.1/31.6	29.1/31.7
Agent frigorific			R32	R32
Conexiuni tevi	lichid / gaz	mm	Φ6.35/Φ9.52	Φ6.35/Φ9.52
Lungime max. traseu/ Dif. Max. traseu		m	25 / 10	25 / 10
Interval functionare	racire/incalzire	° C	-15~-50/-25~30	-15 ~ 50/-25 ~ 30